


 m	SR / DR																				Potain GTMR 400				
	15	16	18	20	22	24	26	28	30	32	33,75	34	36	38	40	42	44	45	46	48	50				
10 - 14 M	9,19	8,37	7,16	6,23	5,5	4,9	4,41	3,99	3,63	3,33	3,09	3,06	2,82	2,61	2,43	2,26	2,11	2,04	1,97	1,85	1,73				
10 - 14,9 M	9,92	9,16	7,85	6,84	6,04	5,39	4,85	4,4	4,02	3,68	3,43	3,39	3,14	2,91	2,71	2,53	2,32	2,28							
10 - 16,2 M	10	10	8,73	7,62	6,73	6,03	5,44	4,94	4,51	4,14	3,86	3,825	3,54	3,29	3,07										
10 - 17,8 M	10	10	9,92	8,67	7,68	6,88	6,21	5,65	5,17	4,76	4,44														

## Technische gegevens

Hijsen	2 Draads		4 Draads	
<b>1e snelheid</b> 	4,4 m/min.	5000 kg	2,2 m/min.	10000 kg
<b>2e snelheid</b> 	24 m/min.	5000 kg	12 m/min.	10000 kg
<b>3e snelheid</b> 	48 m/min.	2500 kg	24 m/min.	5000 kg
<b>Loopkat</b>	7,5 - 30 - 60 m/min.			
<b>Zwenken</b>	0 - 0,7 omw./min.			
<b>Kraanrijden</b>	max. 25 m/min.			
<b>Gronddruk</b>	1,2 kg/cm <sup>2</sup>			
<b>Stroom / spanning</b>	kraan: 3 x 63 Ampere / rijden: 3 x 125 Ampere			
<b>Generatorset</b>	100 KVA			

Haakhoogtes
33.4 m
29.8 m
26.2 m
22.6 m