



	m/t	SR / DR										Teka P356 eLift				
		15	17	19	21	23	25	27	29	31	35	37	40	42	45	
6 - 12,6 M	4,78	4,05	3,53	3,08	2,73	2,42	2,17	1,97	1,79	1,49	1,37	1,21	1,12	1		
6 - 14,3 M	5,62	4,78	4,17	3,65	3,24	2,89	2,61	2,38	2,17	1,82	1,68	1,5				
6 - 15,1 M	6	5,17	4,52	3,96	3,52	3,15	2,84	2,59	2,37	2						
6 - 15,7 M	6	5,44	4,76	4,17	3,71	3,32	3	2,74	2,5							

Technische gegevens					
Hijzen	2 Draads		4 Draads		
1. snelheid 	5,4 m/min.	4000 kg	2,7 m/min.	8000 kg	
2. snelheid 	30 m/min.	4000 kg	15 m/min.	8000 kg	
3. snelheid 	60 m/min.	2000 kg	30 m/min.	4000 kg	
Loopkat	15 - 30 - 58 m/min.				
Zwenken	0 - 0,8 omw./min.				
Kraanrijden	max. 25 m/min.				
Gronddruk	0,85 kg./cm <sup>2</sup>				
Stroom / spanning	kraan: 3 x 63 Ampere / rijden: 3 x 80 Ampere				
Generatorset	100 KVA				