


 t m	SR / DR																		Potain 386 A	
	15	17	19	21	23	25	27	29	31	33	35	37	38	40	42	45	48	50		
8 - 11,7 M	5,78	4,92	4,26	3,74	3,3	2,98	2,69	2,44	2,23	2,05	1,89	1,74	1,68	1,55	1,45	1,3	1,18	1,1		
8 - 13,7 M	7,75	6,07	5,28	4,65	4,15	3,73	3,38	3,08	2,83	2,6	2,41	2,23	2,15	2,01	1,88	1,7				
8 - 15,4 M	8	7,07	6,16	5,44	4,86	4,38	3,98	3,64	3,34	3,09	2,86	2,66	2,58	2,44						
8 - 16,3 M	8	8	6,63	5,86	5,24	4,73	4,3	3,93	3,62	3,34	3,1									
8 - 17,9 M	8	8	7,46	6,6	5,91	5,34	4,86	4,45	4,1											

Technical data					Hook heights → 32.8 m → 29.4 m → 26 m → 22.6 m → 16 m	
Hoisting		2 wires		4 wires		
1st speed		5,4 m/min.	4000 kg	2,7 m/min.		8000 kg
2nd speed		30 m/min.	4000 kg	15 m/min.		8000 kg
3rd speed		60 m/min.	2000 kg	30 m/min.		4000 kg
Trolley		15 - 30 - 58 m/min.				
Slewing		0 - 0.8 rpm				
Travelling		max. 25 m/min.				
Ground pressure		1 kg./cm ²				
Current/Voltage		63 Amps	380 V			
Generator set		100 KVA				

Additional technical data on request