


 t s m	SR / DR																A 45 C	
	15	17	19	21	23	25	27	29	31	33	35	36	37	38	40	41	42	45
12 - 11,7 M	8,88	7,65	6,7	5,95	5,35	4,85	4,43	4,07	3,76	3,49	3,25	3,15	3,04	2,95	2,77	2,69	2,61	2,4
12 - 12 M	9,22	7,94	6,96	6,18	5,55	5,04	4,6	4,23	3,91	3,63	3,39	3,28	3,17	3,07	2,93	2,8		
12 - 12,7 M	9,81	8,45	7,41	6,59	5,92	5,37	4,91	4,51	4,17	3,88	3,63	3,5						
12 - 13 M	10,3	8,59	7,54	6,7	6,03	5,47	5	4,6	4,25									

Technical data						Hook heights 37 m 31 m 26 m 20.5 m 15.2 m			
Hoisting	2 wires			4 wires					
1st speed 	6	m/min.	6000	kg	3		m/min.	12000	kg
2nd speed 	26	m/min.	6000	kg	13		m/min.	12000	kg
3rd speed 	52	m/min.	3000	kg	26		m/min.	6000	kg
Trolley	11 - 22 - 45 m/min.								
Slewing	0 - 0,8 rpm.								
Travelling	max.15 m/min.								
Ground pressure	0,8 kg./cm <sup>2</sup>								
Current/Voltage	63	Amps	380	V					
Generator set	130	KVA							

Additional technical data on request